

TIGER X

0W20 SN

TIGER X-SN is a unique synthetic lubricant specially developed for gasoline engines. A new generation of automotive oils based on revolutionary concepts meeting the performance level required by today's gasoline engines. TIGER X is formulated with fully synthetic group III base oil in combination with leading edge additive technology to provide outstanding results under required services, which enables it to give exceptional performance under most severe operating conditions. Serves as a clear API SN capability and complying with requirements of the latest direct injection engines and conventional engines as well.

APPLICATIONS

This oil is recommended for all gasoline and diesel engines in cars and light industrial vehicles. All turbo charged and multi-valved engines. Suitable & exceeds the performance requirement of most European, Japanese and American car manufacturers. Suitable for most severe operating conditions, on highways, dense city traffic & in extreme weather conditions. This engine oil is perfectly adapted to vehicles equipped with catalysts and using unleaded fuel or liquified petroleum gas.

FEATURES

Easy cold start and ideal lubrication at elevated temperatures, ensures low oil consumption and cold start protection against wear. Ensures sustainable high performance. It has the high viscosity index and excellent stability. Fully miscible with other engine oils. Less oil top-up. Superior antiwear properties protect the engine cleanliness and enhanced performance.

SPECIFICATION LEVEL

TIGER X -SN meets and exceeds the requirements of API SN and can be used in all types of cars and light duty trucks. The product also meets the following OEM's standards. ILSAC GF-4, ILSAC GF-5 energy conservation standards, General Motors GM 6094M specifications,

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.50
Viscosity index	ASTM D2270		160
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	215
TBN	ASTM D2896	mg KOH/g	8.7
Apparent Viscosity, cP	ASTM D5293	mPa.s	4000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Black Tiger

3463 Old Al-Kharj Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia

www.blacktiger.com.sa

