TIGER X 15W40 CI-4/SL

TIGER X-CI-4/SL is a premium top quality Fully synthetic diesel engine oil exceeding the most demanding European speci cations and meeting the market demands for fuel ef cient oils. It is formulated with selected synthetic base uids and additives offering the best performance available for modern diesel engines.

APPLICATIONS

CI-4/SL Fully Synthetic Diesel Engine Oil can be used in the latest highly rated turbo-charged 4 stroke diesel engines under all operating conditions.

FEATURES

Improves piston cleanliness. Outstanding wear protection under all operating conditions. Prevents bore polishing. Superior oxidation & thermal stability. Low oil top-up. Improve cold starting properties.

SPECIFICATION LEVEL

CI-4/SL Fully Synthetic Diesel Engine Oil meets and exceeds the requirements of API CI-4/SL, ACEA E3 E5, M Benz 228.3, VOLVO VDS3, GM Allison C4, MAN 3275, Scania - LDF, Cummins CES 20078, 20071, 20072, 20076 & 20077. Mack Truck: EO-M, EO-M+

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 100°C	ASTM D445	mm2/s	14.5
Viscosity index	ASTM D2270		160
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	230
TBN	ASTM D2896	mg KOH/g	10
Apparent Viscosity, cP	ASTM D5293	mPa.s	4000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

