

TIGER X

15W40 CJ-4

TIGER X-CJ-4 Full Synthetic Heavy Duty Engine Oil is a highly advanced, heavy duty, maximum performance engine oil recommended for modern naturally aspirated and turbocharged four-stroke diesel engines requiring oils meeting API CJ-4 and operating in extreme or challenging climatic conditions.

APPLICATIONS

CJ-4 Full Synthetic Heavy Duty Engine Oil is a premium, mixed meet motor oil recommended for use in naturally aspirated and turbocharged four-stroke diesel engines and four-stroke gasoline engines in which the API CJ-4 service category and SAE 15W-40 viscosity grade are recommended. It is fully compatible with previous API service categories, allowing its use in old and new engines operating in a wide range of service applications and climatic conditions.

FEATURES

Improves piston cleanliness. Outstanding wear protection under all operating conditions. Prevents bore polishing. Superior oxidation & thermal stability. Low oil top-up. Improve cold starting properties.

SPECIFICATION LEVEL

CJ-4 Fully Synthetic Diesel Engine Oil meets and exceeds the requirements of API CI-4/SL, ACEA E3 E5, M Benz 228.3, VOLVO VDS3, GM Allison C4, MAN 3275, Scania - LDF, Cummins CES 20078, 20071, 20072, 20076 & 20077. Mack Truck: EO-M, EO-M+

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	95.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	15.0
Viscosity index	ASTM D2270		165
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	230
TBN	ASTM D2896	mg KOH/g	10
Apparent Viscosity, cP	ASTM D5293	mPa.s	6500

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Black Tiger

3463 Old Al-Kharj Road Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia

www.blacktiger.com.sa

