# TIGER TRANSMISSION OIL 30

TIGER TRANSMISSION OIL 30 SAE 30 transmission lubricant designed specially for extended drain and server service in heavy-duty manual transmission which require a conventional non-EP transmission lubricant. The superior all-season lubricating properties means less friction in the transmission resulting in a potential for improved fuel economy.

## **APPLICATIONS**

TIGER TRANSMISSION OIL 30 is a specially formulated transmission lubricant that meets or exceeds the following performance requirements. Eaton transmission Div., PSO-164 Rev.7 (Not Eaton Listed), API MT-1, Volvo I-shift, ZF freedom Line, Navistar TMS 6816.

# **FEATURES**

TIGER TRANSMISSION OIL 30 is formulated from a highly mineral base stock with a high viscosity index and low pour point to ensure superior year-round performance. Its also contains an anti-wear additive, along with rust, oxidation, and corrosion inhibitors that protect bearings and synchronizers, reduce component wear and promote longer transmission and lubricant life. Additional benefits include. Potential for maximum fuel economy, easier cold weather shifting, all-climate year round performance, extended drain interval.

## SPECIFICATION LEVEL

TIGER TRANSMISSION OIL 30 meet GL-1, GL-3, GL-4 as required.

# TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C, cSt	ASTM D445	mm2/s	81.8
Kinematic viscosity at 100°C, cSt	ASTM D445	mm2/s	10.4
Viscosity index	ASTM D2270		114
Pour point	ASTM D6892	°C	-24
Flash Point COC,	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

