

TIGER PLUS

ATF DEX II

TIGER ATF T-A is AUTOMATIC TRANSMISSION FLUID DEXRON II. It is a superior quality automatic transmission fluid formulated with high viscosity index base oils and selective additive package to obtain anti-wear, anti-oxidant, anti-foam properties and low temperature fluidity. It provide excellent protection against wear and their frictional properties gives consistent and smooth shift under a wide range of driving condition.

APPLICATIONS

TIGER PLUS ATF DEX II is recommended for use in passenger cars and light trucks as well as power steering which require Dexron II D specification fluid. It can also be used in some hydraulic system farm equipment. It is compatible with seal material in transmission unit

FEATURES

Excellent anti-wear, anti-oxidant and anti-friction properties. Excellent low temperature fluidity, thermal and high shear stability. Provides smooth and trouble free operation of ATF. Good frictional properties gives smooth shift performance. Prompt circulation and effective lubrication at low temperature.

SPECIFICATION LEVEL

TIGER PLUS ATF DEX II meets the performance criteria of GM Dexron IID and Dexron IIE, Mercedes Benz 236.7. ALLISON C-3, GM 6137M, Caterpillar TO-2.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		Red
Kinematic viscosity at 100°C, cSt	ASTM D445	mm ² /s	6.5
Viscosity index	ASTM D2270		170
Pour point °C	ASTM D6892	°C	-42
Flash Point COC, °C	ASTM D92	°C	202
Brookfield mPa.s @ -40 °C	ASTM D2983	mPa.s	30,000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Black Tiger

3463 Old Al-Kharj Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia

www.blacktiger.com.sa

