

TIGER

SCOOTER 2T

TIGER SCOOTER 2T is specially blended for two-stroke gasoline lubrication it is inhibited with low ash detergent additives to provides protection against seizure, scuffing and wear. Diluent is added easier mixing with gasoline.

APPLICATIONS

TIGER SCOOTER 2T is designed for use in two stroke air-cooled gasolines. It is also recommended for smaller engines fitted in scooters, motorcycles, lawnmowers, chainsaws and other small equipment. It Should be added with gasoline in the ratio recommended by the equipment manufacturer.

FEATURES

Engine protection : excellent engine performance. Corrosion protection : adequate corrosion protection. Enhanced engine cleanliness. Reduced piston scuffing. Self mixing with leaded & unleaded petrol. Protects against rusting in fresh and salt water.

SPECIFICATION LEVEL

TIGER SCOOTER 2T meets & exceeds the following requirements: - API TC- JASO FC.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	9.1
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	69
Viscosity Index	ASTM D2270		120
Pour point	ASTM D6892	°C	-33
Flash Point COC	ASTM D92	°C	196

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Black Tiger

3463 Old Al-Kharj Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia

www.blacktiger.com.sa

