TIGER
CIRCULATING 150

TIGER Circulating Oils are premium quality mineral oils blended with carefully selected additives for use in circulation systems and certain other industrial applications which do not require oil with EP Properties.

APPLICATIONS

TIGER Circulating Oils are used for machine circulation systems, oil lubricated plain & roller element bearings, Roll-neck bearings. They may also be used as hydraulic fluids, Industrial Gear Lubricants and general purpose oils.

FEATURES

Wide operating temperature range. Anti-corrosion protection for all metal surfaces. Excellent anti-foam and air release properties. Good water separation properties.

SPECIFICATION LEVEL

DIN	51506 VOL	**PNEUROP**	DIN 51.352

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm2/s	150
Kinematic viscosity at 100°C	ASTM D445	mm2/s	14.50
Viscosity index	ASTM D2270		95
Pour point	ASTM D6892	°C	-18
Flash Point COC	ASTM D92	°C	258

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Black Tiger brand and design are registered trademarks of Raf Chemicals - Made in Saudi Arabia

Black Tiger
3463 Old Al-Kharj Road Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia
www.blacktiger.com.sa