

TIGER

CIRCULATING 220

TIGER Circulating Oils are premium quality mineral oils blended with carefully selected additives for use in circulation systems and certain other industrial applications which do not require oil with EP Properties.

APPLICATIONS

TIGER Circulating Oils are used for machine circulation systems, oil lubricated plain & roller element bearings, Roll-neck bearings. They may also be used as hydraulic fluids, Industrial Gear Lubricants and general purpose oils.

FEATURES

Wide operating temperature range. Anti-corrosion protection for all metal surfaces. Excellent anti-foam and air release properties. Good water separation properties.

SPECIFICATION LEVEL

DIN S1506 VOL **PNEUROP** DIN 51.352

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 220 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 18.70 |
| Viscosity index | ASTM D2270 | | 95 |
| Pour point | ASTM D6892 | °C | -15 |
| Flash Point COC | ASTM D92 | °C | 268 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Black Tiger

3463 Old Al-Kharj Road Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia

www.blacktiger.com.sa

