

# TIGER

## COMPRESSOR OIL 32

**TIGER Compressor Oils are premium quality Air Compressor lubricants blended with high quality paraffinic base oils and selected anti-oxidant and rust inhibitors to give low carbon forming tendencies in Air compressor applications. They are designed for use in rotary and reciprocating compressors both for stationary and mobile applications. These oils can also be used in vacuum pumps because of their low volatility.**

### APPLICATIONS

TIGER Compressor Oils can be used in rotary and reciprocating compressors both for stationery and mobile applications. They can also be used in vacuum pumps and screw pumps.

### FEATURES

Very good oxidation resistance. Very good air release and anti-foam properties. Very good rusting and wear protection properties. Maintains internal surface cleanliness. Longer oil drains intervals.

### SPECIFICATION LEVEL

**DIN**                      51506 VOL                      **PNEUROP**                      DIN 51.352

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	5.35
Viscosity index	ASTM D2270		99
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	208
Air release @ 50 oC Max.	ASTM D3427		2.9

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

**Black Tiger**

3463 Old Al-Kharj Road Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia

[www.blacktiger.com.sa](http://www.blacktiger.com.sa)

