## TIGER **COMPRESSOR OIL 68**

TIGER Compressor Oils are premium quality Air Compressor lubricants blended with high quality paraffinic base oils and selected anti-oxidant and rust inhibitors to give low carbon forming tendencies in Air compressor applications. They are designed for use in rotary and reciprocating compressors both for stationary and mobile applications. These oils can also be used in vacuum pumps because of their low volatility.

## **APPLICATIONS**

TIGER Compressor Oils can be used in rotary and reciprocating compressors both for stationery and mobile applications. They can also be used in vacuum pumps and screw pumps.

## **FEATURES**

**Black Tiger** 

www.blacktiger.com.sa

Very good oxidation resistance. Very good air release and anti-foam properties. Very good rusting and wear protection properties. Maintains internal surface cleanliness. Longer oil drains intervals.

| SPECIFICATION LEVELDIN51506 VOL | PNEUROP    | DIN 51.352 |                 |
|---------------------------------|------------|------------|-----------------|
| TYPICAL CHARACTERISTICS         |            |            |                 |
| Test                            | Method     | Unit       | Average results |
| Kinematic viscosity at 40°C     | ASTM D445  | mm2/s      | 68              |
| Kinematic viscosity at 100°C    | ASTM D445  | mm2/s      | 8.65            |
| Viscosity index                 | ASTM D2270 |            | 98              |
| Pour point                      | ASTM D6892 | °C         | -24             |
| Flash Point COC                 | ASTM D92   | °C         | 234             |
| Air release @ 50 oC Max.        | ASTM D3427 |            | 6.2             |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.



