

TIGER

MARI 30 6 TBN

MARI is premium quality marine oil lubricant for crosshead diesel engine crankcase system. It is especially effective in highly rated crosshead engines with oil cooled pistons, power take- off (PTO) gear applications.

APPLICATIONS

MARI can be used for crankcase lubrication of high power low speed crosshead marine diesel engines. It can be used in stationery diesel engines for power generation and reduction gear boxes.

FEATURES

Good Alkalinity. Excellent resistance to corrosion. Excellent detergency to keeps crankcase and under piston spaces clean. Good oxidation stability.

SPECIFICATION LEVEL

MARI meets API service classification of CD and MIL-L-2104C.

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 110 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 12.0 |
| Viscosity Index | ASTM D2270 | | 98 |
| Pour point | ASTM D6892 | °C | -24 |
| Flash Point COC | ASTM D92 | °C | 230 |
| TBN, mg KOH | | gm | 6 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Black Tiger

3463 Old Al-Kharj Road Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia

www.blacktiger.com.sa

