

TIGER

GEARO EP GL-5 140

TIGER GEARO EP GL-5 blended with highly refined mineral base oil and selective additives for use in heavy duty operations are used in commercial fleet, manual transmission, axles and final drives. Protects from rust & corrosion and low temperature properties, gives good start in cold weather.

APPLICATIONS

TIGER GEARO EP - GL-5 Gear Lubricants are recommended for use in Hypoid gears, compatible with seal and gasket material used in automotive gears. Drive axle, trucks, and taxicabs, contracting and farming equipment.

FEATURES

Excellent anti-wear and anti-rust characteristics, Resistance to oxidation and oil thickening, Maximize equipment life and assist smooth shifting in manual transmission, Outstanding performance against low speed/high torque wear and high speed scoring, Protects against corrosion of ferrous and non-ferrous components, Excellent load carrying capability in severe operating conditions, Compatible with all type of seals to avoid leakage.

SPECIFICATION LEVEL

TIGER GEARO EP - GL-5 GEAR Lube meets API service categories GL-5 and U. S Military specification MIL-L-2105D.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	30.00
Viscosity Index	ASTM D2270		95
Pour point	ASTM D6892	°C	-12
Flash Point COC	ASTM D92	°C	258

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Black Tiger

3463 Old Al-Kharj Hyt, Unit 1, Riyadh 14371-6749 Saudi Arabia

www.blacktiger.com.sa

